


DEGASi®

Product Program

Degassing & Debubbling

NO TROUBLES WITH BUBBLES®





Degasser selection guide

FLOW CAPACITY TO AVOID FORMATION OF BUBBLES

Bubbles are detrimental to any fluidic system. Negative pressure transients, heating or mixing solvents reduces gas solubility and causes off-gassing which can lead to bubble formation. Removing up to 50% of dissolved gases with a Biotech DEGASi® in-line degasser effectively prevents bubble formation even in your most demanding applications. Critical factors for choosing the right degasser include flow rate and composition of the liquid. Optimal flow rates to achieve 50% removal are illustrated below. The Constant Vacuum Degassing Control System makes the DEGASi[®] virtually silent.

BIOCOMPATIBLE FLOW PATH

METAL-FREE

Suitable for proteins, DNA and other biological materials that may adhere to metal surfaces. Not to be used with alkanes like hexane.

0.1



DEGASi



bioCOMPACT

BIOTECH FLUIDICS DEGASi



BIOTECH FLUIDICS DEGASi GPC



DEGASi® Plus series

DEGASi

SEMI-PREP

6

DEGASi

GPC SEMI-PREP



DEGASi® Integration series



DEGASi® Prep & Prep+



<1000

DEGASi

100





HIGH FLOW RATES

FOR WATER-BASED SOLUTIONS DEGASi® High Flow 1000 with ultra-high degassing efficiency works at flow rates up to 1000 ml/min. Designed for water and water-based solutions like buffers. Can be used with up to 5% water soluble organic solvents.

GPC-COMPLIANT FLOW PATH

FOR ANY ORGANIC SOLVENT

GPC-compatible chambers tolerate all common organic solvents including alkanes (hexane, heptane, pentane) and are the recommended choice for DCM, THF, acetone etc. Applications involving Hexafluoroisopropanol (HFIP) require DEGASi® HFIP.


15

DEGASi

Flow rate in mL/min

Product details on the back

Let us help you find the right degasser. biotechfluidics.com



GETTING RID OF BUBBLES - HOW IT WORKS

Biotech DEGASi® degassers use a Systec® AF gas permeable membrane with a Constant Vacuum Degassing Control System to extract dissolved gasses out of fluid. The extracted gasses are evacuated through an exhaust outlet.

| DEGASi® product Teflon AF-based | 50% de- gassing mL/min | Max. flow rate mL/min | ID mm | Swept volume ul | Max. fluid pressure bar (psi) | no. of channels | Solvent compatibility | | | Part number |
|---------------------------------|------------------------------|-----------------------------|----------|-----------------------|-------------------------------------|--------------------|-----------------------|---------|------|-------------------|
| | | | | | | | Bio-comp. | Alkanes | HFIP | x= no of channels |
| DEGASi® Plus serie | es | | | | | | | | | |
| Nano | 0.1 | 0.3 | 0.30 | 25 | 1.8 (27) | 1-6 | Yes | No | No | 0003-635X-N |
| Micro | 0.5 | 10 | 1.14 | 100 | 5 (70) | 1-6 | Yes | No | No | 0003-635X-S |
| Classic | 3 | 10 | 1.14 | 480 | 5 (70) | 1-6 | Yes | No | No | 0003-635X-A |
| GPC | 3 | 10 | 1.14 | 480 | 5 (70) | 1-6 | No | Yes | No | 0003-662X-B |
| Semi-Prep | 6 | 10 | 1.14 | 925 | 5 (70) | 1-6 | Yes | No | No | 0003-635X-L |
| GPC Semi-Prep | 6 | 10 | 1.14 | 925 | 5 (70) | 1-6 | No | Yes | No | 0003-662X-L |
| DEGASi® Integration | on series | | | | | | | | | |
| Nano | 0.1 | 0.3 | 0.30 | 25 | 1.8 (27) | 1-5 | Yes | No | No | 0001-635X-BN |
| Micro | 0.5 | 10 | 1.14 | 100 | 5 (70) | 1-5 | Yes | No | No | 0001-635X-BS |
| Classic | 3 | 10 | 1.14 | 480 | 5 (70) | 1-5 | Yes | No | No | 0001-635X-BA |
| GPC | 3 | 10 | 1.14 | 480 | 5 (70) | 1-5 | No | Yes | No | 0001-662X-B |
| Semi-Prep | 6 | 10 | 1.14 | 925 | 5 (70) | 1-5 | Yes | No | No | 0001-635X-BL |
| GPC Semi-Prep | 6 | 10 | 1.14 | 925 | 5 (70) | 1-5 | No | Yes | No | 0001-662X-BL |
| HFIP | 3 | 10 | 1.14 | 480 | 5 (70) | 1-5 | No | Yes | Yes | 0001-662X-HFIP |
| HFIP Semi-Prep | 6 | 10 | 1.14 | 925 | 5 (70) | 1-5 | No | Yes | Yes | 0001-662X-HFIP-L |
| DEGASi® BioComp | act | | | | | | | | | |
| BioCompact | 2 | 4 | 0.89 | 285 | 3 (50) | 1-6 | Yes | Yes | No | 0004-X285 |
| DEGASi® Preparati | ve series | | | | | | | | | |
| Prep | 15 | 50 | 1.92 | 5.4 mL | 5 (70) | 2 or 4 | No | Yes | No | 0041-X053 |
| Prep+ | 75 | 100 | NA | 22 mL | 3 (50) | 1, 2 or 4 | No | Yes | No | 0001-0X20 |
| Prep+ Large*/XL | 100 | 200 | NA | 22 mL | 3 (50) | 1, 2 or 4 | No | Yes | No | 0001-0X20-Lor XL |
| Prep+ AUX** | 75/100 | 100/200 | NA | 22 mL | 3 (50) | 1, 2 or 4 | No | Yes | No | 0001-0X20-SH |
| High Flow 1000*** | 1000 | 2000 | NA | 200 mL | 1 (14) | 1 | Yes | No | No | 0003-HF.1000 |

Fluidic connectors are 1/4"-28 female flatbottom unless otherwise stated.

*Large; 5/16"-24 flat bottom female **To be complimented with any connectors for 3/16" tubing. XLarge; 1/2"-20 flat bottom female DEGASi® Nano; 10-32 coned port. connectors for 1/4" tubing.

extra degassing chamber from DEGASi Plus (Micro, Classic, GPC, Semi-Prep or GPC Semi-Prep).

*** Silicone degassing membrane only for water-based solutions and buffers. Barbed end connectors for ID 8 mm tubing.

For ordering and technical support, please contact:

Europe: Biotech Fluidics AB | Tel:+46 (0)300 56 91 80 | info@biotechfluidics.com USA: Biotech Fluidics LLC | Tel: +1 612 703 5718 | sales@biotechfluidics.com Japan: BioNik Inc. | Tel: +81 545 38 9125 | info@bionikinc.com

