


Flexible Fused Silica Capillary Tubing

- **TSP:** Standard Polyimide Coating
- **TSG:** High Temperature Polyimide Coating
- **TSU:** UV Transparent Coating

Standard Capillary Tubing Sizes

New Tighter Tolerances!!

Product Descriptor	ID μm	OD μm	CT* μm
TSP002150	002 ± 01	150 ± 06	12
TSP005150	005 ± 02	150 ± 06	12
TSP005375	005 ± 02	363 ± 10	20
TSP010150	010 ± 02	150 ± 06	12
TSP010375	010 ± 02	363 ± 10	20
TSP015150	015 ± 02	150 ± 06	16
TSP015375	015 ± 02	363 ± 10	20
TSP020090	020 ± 02	090 ± 06	12
TSP020150	020 ± 02	150 ± 06	12
TSP020375	020 ± 02	363 ± 10	20
TSP025150	025 ± 02	150 ± 06	12
TSP025375	025 ± 02	363 ± 10	20
TSP030150	030 ± 03	150 ± 06	12
TSP030375	030 ± 03	363 ± 10	20
TSP040105	040 ± 03	105 ± 06	12
TSP040150	040 ± 03	150 ± 06	12
TSP040375	040 ± 03	363 ± 10	16
TSP050150	050 ± 03	150 ± 06	12
TSP050192	050 ± 03	186 ± 06	16
TSP050375	050 ± 03	363 ± 10	20
TSP075150	075 ± 03	150 ± 06	12
TSP075200	075 ± 03	193 ± 07	12
TSP075375	075 ± 03	363 ± 10	20
TSP100170	100 ± 04	164 ± 06	12
TSP100200	100 ± 04	193 ± 07	12
TSP100245	100 ± 04	238 ± 07	16
TSP100375	100 ± 04	363 ± 10	20
TSP150375	150 ± 04	363 ± 10	20
TSP180350	180 ± 06	340 ± 10	18
TSP250350	250 ± 06	360 ± 10	18
TSP320450	320 ± 06	435 ± 15	18
TSP530660	536 ± 06	665 ± 15	24
TSP530700	530 ± 10	700 ± 20	24
TSP700850	700 ± 10	850 ± 20	24
TSG250350	250 ± 06	350 ± 15	20
TSG320450	320 ± 06	435 ± 15	18
TSG530660	536 ± 06	673 ± 25	18
TSU075375	075 ± 03	363 ± 10	15
TSU100375	100 ± 04	363 ± 10	15



TSP Characteristics

- Standard polyimide coating
- Synthetic fused silica
- 100% proof tested at 100kpsi**
- Operation up to 350°C

TSG Characteristics

- High temperature polyimide coating
- Synthetic fused silica
- 100% proof tested at 100kpsi**
- Operation up to 400°C

TSU Characteristics

- UV transparent coating
- Synthetic fused silica
- Operation up to 160°C

Custom Sizes & Coatings Available



18019 N. 25th Avenue • Phoenix, AZ 85023-1200
 Voice: (602) 375-4100 Fax: (602) 375-4110
 E-Mail: sales@polymicro.com
 URL: <http://www.polymicro.com>

- Flexible Capillary
- Multimode Optical Fiber
- Specialty Assemblies
- Micro-Components