
Hand-Tight Fitting with Ti-LOK™ Ferrule for PEEKsil™

The EXP2 Fittings with Ti-LOK Ferrules offer UHPLC connections for 1/16" and 1/32" PEEKsil tubing that seal to 15,000+ psi – depending on the tubing I.D. For example, 50µm PEEKsil tubing can be hand tightened to over 20,000 psi. These fittings are ideal for making Nano HPLC and UHPLC connections and easily fit into tight spaces such as injection valves, column couplers, sample loops and column ovens.

The EXP2 titanium hybrid Ti-LOK ferrules combine the robustness of titanium and the sealing capability of PEEK. Utilizing a unique inverted geometric design, the ferrules firmly press the PEEKsil tubing against the tube stop of any instrument port, creating a zero dead volume (ZDV) connection. The titanium portion of the ferrule does not permanently swage to the tubing, allowing for many repeat connections and the ability to adjust the tubing to different port depths. Included with the Ti-LOK ferrules are the new EXP2 3/16" hex head nuts and EXP2 Driver. The nuts are available with 6-32, 6-40 and 10-32 threads and have been scaled down to allow for maximum working room in cramped spaces. The EXP2 Driver is a small, easy to use knurled torque driver which snaps on to the nuts for hand-tightening and loosening. The EXP2 Driver is slotted and can be removed from the nut and tubing after use. EXP2 Ti-LOK fittings are currently available as kits with EXP2 nuts, Ti-LOK ferrules and EXP2 Driver.

The combination of bottom-of-the-port sealing, Titanium Hybrid technology and precision manufacturing make the EXP2 Fittings an unbeatable choice for any standard or nano UHPLC and UHPLC/MS application.



Features

- Rated Hand-Tight to 20,000+ psi (1,400+ bar)
- Auto-adjusting, zero-dead-volume connection
- Extremely robust one-piece ferrule design
- Intended for many repeat uses
- Cost efficent with replaceable components
- Perfect for standard or nano UHPLC and UHPLC/MS
- Made in U.S.A.

8,201,854 and other U.S Patents Pending PEEKsil™ is a registered trademark of SGE Analytical Science

EXP2 Fitting Kit Configurations

Includes 2 Ti-LOK Ferrules, 2 EXP2 Nuts + 1 EXP2 Driver

15-19-04930 6-32 THD Nuts for 1/32" OD PEEKsil 15-19-04931 6-40 THD Nuts for 1/32" OD PEEKsil 15-20-04932 10-32 THD Nuts for 1/16" OD PEEKsil

Includes 10 Ti-LOK Ferrules, 10 EXP2 Nuts + 1 EXP2 Driver

15-19-04929 6-32 THD Nuts for 1/32" OD PEEKsil 15-19-04927 6-40 THD Nuts for 1/32" OD PEEKsil 15-20-04920 10-32 THD Nuts for 1/16" OD PEEKsil

